





Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs.

From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

STX OD

G-Snack Ten (X) Touch Outdoor

TECHNICAL SPECIFICATIONS	STX OD
DIMENSIONS H x W x D (mm)	1900 x 1200 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	540 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	F (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1921 (Cat. 2) 2276 (Cat. 3) 2279 (Cat. 4)

 ${\small @ {\sf SandenVendo GmbH}}$

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.







Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs.

From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST8 OD

G-Snack Eight (VIII) Touch Outdoor

TECHNICAL SPECIFICATIONS	ST8 OD
DIMENSIONS H x W x D (mm)	1900 x 1030 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 56
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	540 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	E (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1492 (Cat. 2) 2151 (Cat. 3) 2122 (Cat. 4)

 ${\small @ {\sf SandenVendo GmbH}}$

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.







Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs.

From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST6 OD

G-Snack Six (VI) Touch Outdoor

TECHNICAL SPECIFICATIONS	ST6 OD
DIMENSIONS H x W x D (mm)	1900 x 890 x 1010
WEIGHT (NET - Standard machine without options)	325 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 42
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
MAX. POWER CONSUMPTION	540 W
POWER SUPPLY	230/240 V - 50/60 Hz

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.